

Multi-purpose Examination Table

G110202 1600 and G110202 2000 with 450-750mm up/down movement



Ideal for use in endoscopy, colonoscopy, radiology and pain clinics.

Features

- Battery powered - fully portable.
- Motorized working height adjustment from 45 to 75 cm
- Motorized $\pm 10^\circ$ Trendelenburg
- 3 programmable working heights
- Floating 80x30 cm X-ray transparent tabletop with electromagnetic locks
- Tabletop: G110202 1600 = 200 x 80 cm - X-ray transparent area: 197 x 65 cm
- Tabletop: G110202 2000 = 200 x 65 cm - X-ray transparent area: 197 x 50 cm
- Flexible control panel on side rail
- Additional back-up battery with wall charger
- Big castors with central lock
- Weight capacity up to 250 kg



Control panel

OPTIONS

- Side guards
- Drip stand
- Mattress 3 or 5cm
- Positioning handles
- Paper roll holder
- Arm support
- Working height 50 x 90 cm
- Working height 60 x 85 cm
- Working height 65 x 95 cm
- Working height 70 x 105 cm



Technical data:

- Table frame is made of steel and painted off white
- Distance between columns 118 cm
- Tabletop 200X80cm and 200X65cm
- Flat tabletop, with stainless steel side rails and alu. Rails for equipment
- Tabletop made of composite material, al-equivalent app. 0,9mm al.
- Motorized battery supplied vertical tabletop movement 45cm-75cm
- Motorized battery supplied Trendelenburg movement 10+-gr.
- On board 24V interchangeable battery for vertical movements and Trendelenburg
- Wall mounted charger 230/24V and extra 24V battery
- Battery capacity at least 50 times tabletop up and down movement, before changing with the reloaded battery
- Tabletop longitudinal movement +- 37cm with magnet brake
- Tabletop transversal movement +- 15cm with magnet brake
- Moving force to move the tabletop with a 100kg. patient: 100 grams
- Control panel for control of tabletop movement
- 150mm wheels with central triple-function foot brake, total lock, free and direction lock.
- Rubber brake pedals to avoid damage of ankles and legs
- Weight of table: 135kg
- Max. Weight of patient: 250kg.
- One year of warranty
- Manufactured according to CE directive with CE-approval
- Manufactured in Denmark